



STATIKIL PE

Topical anti-stat formulated for PE gas piping



- Effectively eliminates static charges on PE gas pipe by increasing surface conductivity
- Eliminates need for bulky burlap or pipe wraps
Keeps work area clear and eliminates trip hazards posed by other ground pipe “wraps”
- To be used prior to construction operations including squeeze-off, repair, tapping, cutting, venting, etc.
- Colorant added for positive verification of product coverage
- Remains effective even after pipe is dry

Product available ready for use as follows:

- 32 oz spray bottle
- 1 & 5 Gallon containers
- 55 Gallon Drum

STATIKIL PE has been tested by independent laboratories and meets or exceeds ASTM D-257-80, MIL B-81705-B, Electronic Industry IS-5 and NFPA-99 specifications for surface resistivity and static decay.

Health 0	Flammability 0
Reactivity 0	



Specifications

Composition	High Molecular Weight Tropical Antistat
STATIKIL PE Physical Form	Liquid
Color	Gray Pigment for Visibility
Flash Point	None
Freeze Point	-10° F
Explosion Hazard	None
Specific Gravity	1.0
Odor	Mild Lemon
pH Regular	7.71
Static Decay Rate	MIL-B-81705-B At Relative Humidity @13% 72° F .35 Sec @5 KV

PLEASE VISIT WWW.STATIKILPE.COM TO SEE A VIDEO OF STATIKIL PE IN ACTION!

Distributed by:



9 Mars Court
Boonton Twp, NJ 07005
t: 973-335-4800
f: 973-402-1558
www.mulcare.com

MANUFACTURED BY

